

TECHNICAL DATASHEET		
EGGER LAMINATE FLOORING		
Coreboard		HDF swell stopp plus
Profil		The patented EGGER installation system JUST clic! stands for quick and simple installation process without glue. Patented as JUST clic! EP 1 441 087 and EP 1 462
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use	31	
European Norm EN13329		
Format	CLASSIC	
Dimension mm (length x width)	1292 x 192	
Complete thickness	8	
Thickness of silenzio® special cellulose Bevel	-	
	Packaging	
Pallet	One-way-pallet	
Paket information		
	Piece	8
	m2	1,98
	kg	13,90
Pallet information		
	Piece	480
	m2	119,07
	kg	849,00
	Classification and general requirements	
abrasion resistance according EN13329	AC3 (P ≥ 2000)	
impact resistance according EN13329	IC1	
resistance to staining EN438	group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425	No change in appearance or damage	
Castor chairs according EN12529	Type W	
Thickness swelling according EN13329	≤ 18 %	
tolerance of top layer according EN13329	length ± 0,2 mm width ± 0,1 mm thickness ± 0,5 mm	
Light fastness according EN13329	blue wool scale ≥ level 6 grey wool scale ≥ level 4	
Static indentation by constant pressure according EN13329	< 0,01	
Surface soundness according EN13329	≥ 1,0 N/mm2	
Thermal resistance according to EN 12667	0,07 m² K/W	



TECHNICAL DATASHEET			
EGGER LAMINATE FLOORING			
Coreboard		HDF swell stopp plus	
Profil		The patented UNI <i>fit!</i> installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.	
Guarantee domestic area		according to Egger Guarantee	
Guarantee comercial area		according to Egger Guarantee	
Antistatic properties according EN1815		yes, < 2 kV	
Class of use	32		
European Norm EN13329			
Format	CLASSIC		
Dimension mm (length x width)	1291 x 193		
Complete thickness	8		
Thickness of silenzio® special cellulose Bevel	-	WV2	WV4
Packaging			
Pallet	One-way-pallet		
Paket information			
	Piece	8	
	m2	1,99	
	kg	13,86	
Pallet information			
	Piece	480	
	m2	119,40	
	kg	850,00	
Classification and general requirements			
abrasion resistance according EN13329	AC4 (IP ≥ 4000)		
impact resistance according EN13329	IC2		
resistance to staining EN438	group 1 + 2: level 5 group 3: level 4		
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact		
Effect of a castor chair according EN425	No change in appearance or damage		
Castor chairs according EN12529	Type W		
Thickness swelling according EN13329	≤ 18 %		
tolerance of top layer according EN13329	length ± 0,2 mm width ± 0,1 mm thickness ± 0,5 mm		
Light fastness according EN13329	blue wool scale ≥ level 6 grey wool scale ≥ level 4		
Static indentation by constant pressure according EN13329	< 0,01		
Surface soundness according EN13329	≥ 1,0 N/mm ²		
Thermal resistance according to EN 12667	0,07 m ² K/W		



TECHNICAL DATASHEET	
EGGER LAMINATE FLOORING	
Coreboard	HDF Aqua Plus
Profil	The patented UNI <i>fit!</i> installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area	according to Egger Guarantee
Guarantee comercial area	according to Egger Guarantee
Antistatic properties according EN1815	yes, < 2 kV
Class of use	32
European Norm EN13329	
Format	CLASSIC
Dimension mm (length x width)	1291 x 193
Complete thickness	8
Thickness of silenzio® special cellulose	
Bevel	WV4
Paket information	Packaging One-way-pallet
Piece	8
m2	1,99
kg	14,66
Pallet information	
Piece	480,00
m2	119,60
kg	898,00
Classification and general requirements	
abrasion resistance according EN13329	AC4 (IP ≥ 4000)
impact resistance according EN13329	IC2
resistance to staining EN438	group 1 + 2: level 5 group 3: level 4
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact
Effect of a castor chair according EN425	No change in appearance or damage
Castor chairs according EN12529	Type W
Thickness swelling according EN13329	≤ 5 %
tolerance of top layer according EN13329	length ± 0,2 mm width ± 0,1 mm thickness ± 0,5 mm
Light fastness according EN13329	blue wool scale ≥ level 6 grey wool scale ≥ level 4
Static indentation by constant pressure according EN13329	< 0,01
Surface soundness according EN13329	≥ 1,0 N/mm2
Thermal resistance according to EN 12667	0,06 m² K/W



TECHNICAL DATASHEET		
EGGER LAMINATE FLOORING		
Coreboard		HDF swell stopp plus
Profil		The patented UNI <i>fit!</i> installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use	32	
European Norm EN13329		
Format	MEDIUM	
Dimension mm (length x width)	1291 x 135	
Complete thickness	11	
Thickness of silenzio® special cellulose		
Bevel	WV4	
	Packaging	
Pallet	One-way-pallet	
Paket information		
	Piece	6
	m2	1,05
	kg	10,14
Pallet information		
	Piece	450
	m2	78,43
	kg	774,00
Classification and general requirements		
abrasion resistance according EN13329	AC4 (IP ≥ 4000)	
impact resistance according EN13329	IC2	
resistance to staining EN438	group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425	No change in appearance or damage	
Castor chairs according EN12529	Type W	
Thickness swelling according EN13329	≤ 18 %	
tolerance of top layer according EN13329	length ± 0,2 mm width ± 0,1 mm thickness ± 0,5 mm	
Light fastness according EN13329	blue wool scale ≥ level 6 grey wool scale ≥ level 4	
Static indentation by constant pressure according EN13329	< 0,01	
Surface soundness according EN13329	≥ 1,0 N/mm2	
Thermal resistance according to EN 12667	0,12 m² K/W	



TECHNICAL DATASHEET		
EGGER LAMINATE FLOORING		
Coreboard		HDF swell stopp plus
Profil		The patented UNI <i>fit!</i> installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use		32
European Norm EN13329		
Format		LARGE
Dimension mm (length x width)		1291 x 246
Complete thickness		8
Thickness of silenzio® special cellulose		
Bevel		WV4
		Packaging
Pallet		One-way-pallet
Paket information		
	Piece	8
	m ²	2,54
	kg	18,00
Pallet information		
	Piece	360
	m ²	114,30
	kg	822,00
Classification and general requirements		
abrasion resistance according EN13329		AC4 (IP ≥ 4000)
impact resistance according EN13329		IC2
resistance to staining EN438		group 1 + 2: level 5 group 3: level 4
Effect of furniture leg according EN424		No damage shall be visible, when tested with foot Type 0 artefact
Effect of a castor chair according EN425		No change in appearance or damage
Castor chairs according EN12529		Type W
Thickness swelling according EN13329		≤ 18 %
tolerance of top layer according EN13329		length ± 0,2 mm width ± 0,1 mm thickness ± 0,5 mm
Light fastness according EN13329		blue wool scale ≥ level 6 grey wool scale ≥ level 4
Static indentation by constant pressure according EN13329		< 0,01
Surface soundness according EN13329		≥ 1,0 N/mm ²
Thermal resistance according to EN 12667		0,07 m ² K/W



TECHNICAL DATASHEET		
EGGER LAMINATE FLOORING		
Coreboard		HDF swell stopp plus
Profil		The patented UNI <i>fit!</i> installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use	32	
European Norm EN13329		
Format	KINGSIZE	
Dimension mm (length x width)	1291 x 327	
Complete thickness	8	
Thickness of silenzio® special cellulose		
Bevel	WV2	
Packaging		
Pallet	One-way-pallet	
Paket information		
	Piece	6
	m2	2,53
	kg	17,84
Pallet information		
	Piece	240
	m2	101,20
	kg	727,00
Classification and general requirements		
abrasion resistance according EN13329	AC4 (IP ≥ 4000)	
impact resistance according EN13329	IC2	
resistance to staining EN438	group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425	No change in appearance or damage	
Castor chairs according EN12529	Type W	
Thickness swelling according EN13329	≤ 18 %	
tolerance of top layer according EN13329	length ± 0,2 mm width ± 0,1 mm thickness ± 0,5 mm	
Light fastness according EN13329	blue wool scale ≥ level 6 grey wool scale ≥ level 4	
Static indentation by constant pressure according EN13329	< 0,01	
Surface soundness according EN13329	≥ 1,0 N/mm2	
Thermal resistance according to EN 12667	0,07 m² K/W	



TECHNICAL DATASHEET		
EGGER LAMINATE FLOORING		
Coreboard		HDF swell stopp plus
Profil		The patented UNI <i>fit!</i> installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use	32	
European Norm EN13329		
Format	LONG	
Dimension mm (length x width)	2052 x 248	
Complete thickness	9	
Thickness of silenzio® special cellulose		
Bevel	WV4	
Pallet	Packaging One-way-pallet	
Paket information		
	Piece	5
	m2	2,54
	kg	22,12
Pallet information		
	Piece	180
	m2	91,60
	kg	824,00
Classification and general requirements		
abrasion resistance according EN13329	AC4 (IP ≥ 4000)	
impact resistance according EN13329	IC2	
resistance to staining EN438	group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425	No change in appearance or damage	
Castor chairs according EN12529	Type W	
Thickness swelling according EN13329	≤ 18 %	
tolerance of top layer according EN13329	length ± 0,2 mm width ± 0,1 mm thickness ± 0,5 mm	
Light fastness according EN13329	blue wool scale ≥ level 6 grey wool scale ≥ level 4	
Static indentation by constant pressure according EN13329	< 0,01	
Surface soundness according EN13329	≥ 1,0 N/mm2	
Thermal resistance according to EN 12667	0,08 m² K/W	



TECHNICAL DATASHEET		
EGGER LAMINATE FLOORING		
Coreboard		HDF swell stopp plus
Profil		The patented UNI <i>fit!</i> installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use		33
European Norm EN13329		
Format		CLASSIC
Dimension mm (length x width)		1291 x 193
Complete thickness		11
Thickness of silenzio® special cellulose		
Bevel		WV4
		Packaging
Pallet		One-way-pallet
Paket information		
	Piece	6
	m2	1,49
	kg	14,69
Pallet information		
	Piece	312
	m2	77,74
	kg	778,00
Classification and general requirements		
abrasion resistance according EN13329		AC5 (IP ≥ 6000)
impact resistance according EN13329		IC3
resistance to staining EN438		group 1 + 2: level 5 group 3: level 4
Effect of furniture leg according EN424		No damage shall be visible, when tested with foot Type 0 artefact
Effect of a castor chair according EN425		No change in appearance or damage
Castor chairs according EN12529		Type W
Thickness swelling according EN13329		≤ 18 %
tolerance of top layer according EN13329		length ± 0,2 mm width ± 0,1 mm thickness ± 0,5 mm
Light fastness according EN13329		blue wool scale ≥ level 6 grey wool scale ≥ level 4
Static indentation by constant pressure according EN13329		< 0,01
Surface soundness according EN13329		≥ 1,0 N/mm2
Thermal resistance according to EN 12667		0,12 m² K/W

